## DP200-IB

Second generation USB sanitation terminal. Improved performance, support for USB 3.0, increased resilience to USB-kill attacks and enhanced virtual separation has been added in the second generation.

The terminal is a security platform which can run different types of security utilities. Choose from several functions that are pre-installed into the platform, including multiple Anti-Virus engines, Content Disarm and Reconstruction (CDR), whitelist for file types as well as for attached USB hardware.





Scan the QR-code for more information



PRODUCT INFORMATION	
Chassis	
Case	Bent sheet metal
Front	CNC milled Aluminum
Display	LCD - monochrome 2x16
Security	
Write protection	Software
USB blocking	Hardware
Administration	Hardware & Software
Antivirus engines	Multiple
CDR	Optional
Operating system	Virtualized Linux
CPU	
intel Core up to	i5 gen 12
Memory	
RAM up to	32 GB
Interfaces	
USB	3.0 Туре-А
Ethernet	N/A
Size	
Dimensions (W x D x H)	180 x 328 x 104 mm
Temperature Range	
Operational	0°C to 40°C (relative humidity 20-90%)
Storage	-20°C to +60°C
Power	
AC Adapter	19V, 4.74A, 90 W
Standards	
CE	EN 55024:2010 (A1:2015), EN 61000-6-3:2007(A1:2011)
REACH	Yes
Tempest	Optional Level A
Warranty	1 year

